



**Wheeled Fire Extinguisher 300 lb. Direct Pressure
Model: 493 PURPLE K Dry Chemical
Specifications**

SPECIFICATIONS	125/150 LB. DRY CHEMICAL			300/350 LB. DRY CHEMICAL		
Model Number	450	451	452	491	492	493
Agent	ABC	REGULAR	PURPLE K	ABC	REGULAR	PURPLE K
U/L Rating	40A:240B:C	240B:C	320B:C	40A:320B:C	320B:C	320B:C
Capacity (lb./ kg)	125 / 57	150 / 68	125 / 57	300 / 136.07	350 / 158.75	300 / 136.07
Shipping Weight (lb./ kg)	335 / 152	360 / 163	335 / 152	743 / 337.01	793 / 359.69	743 / 337.01
Discharge Time (sec.)	52	60	53	60	70	67
Discharge Range (ft./ m)	30 - 40 / 9 - 12					
Nitrogen Cylinder (cu. ft./ litre)	23 / 651			55 / 1557.43		
Operating Temp. Range (F/ C)	- 65° to + 120° / -54° to + 49°					
Safety Disc Burst Range (psii/ kPa)	400 - 500 / 2760 - 3450					
Hose Length (ft./m)	50 / 15.24					
Hose Diameter (in./ cm)	.75 / 1.90			1 / 2.54		
Wheels [Semi-Pneumatic] (in./ cm) [Steel] 9in./cm)	16 x 4 / 40.64 x 10.16			36 x 6 / 91.44 x 15.24		
Height (in./ cm)	45 / 115			57 / 144.78		
Width (in./ cm)	24 / 61			34 / 86.36		
Depth (in./ cm)	36 / 92			39 / 99.06		
Coast Guard Approved	YES					
F.M. Approved			YES			YES